

## DATA SYSTEMS



# PRO 370 PRO 550

**Turnkey Systems**  
Ready for Next Generation Satellites  
S / X / Ka-band




### SATELLITE TRACKING SOLUTIONS

PRO Series antennas are the flagship antenna systems of Safran Data Systems. Their **state-of-the-art technology and full motion tracking capabilities** have made them successful worldwide.

The PRO Series is defined as a **fully capable complete package including all capabilities** (simultaneous dual polarization, single channel monopulse tracking and test capabilities in all band), baseband equipment and services. It ensures our customers a smooth deployment, easy operational start and a long service life in all environments.



Scientific  
Missions



Earth  
Observation  
Satellites



Service  
Providers

#### TRI-BAND S / X / KA

Safran Data Systems Patented  
Concentric Feed

#### HEXAPOD PEDESTAL

Safran Data Systems Patented  
Solution Targeting any point in  
the 360° Hemisphere

#### CORTEX SERIES BASEBAND

The Space Community  
Standard

#### 100% IN-HOUSE COMPONENTS

High Performance

#### SATELLITE AGNOSTIC

Versatile Architecture

**THE RESILIENT ASSET  
FOR THE NEW STANDARDS**

# PRO 370 / PRO 550

	MODEL	PRO 370	PRO 550
	DIAMETER	3.7m (12 ft)	5.5m (18 ft)
	CONFIGURATION	S+Ka	X or S+X or S+Ka or S+X+Ka
S-Band Rx [2.200 – 2.300 GHz] Tx [2.025 – 2.120 GHz]	G/T Mid-Band, 5° Elevation, Clear Sky, +20°C, Continental	>13 dB/K	>16 dB/K
	Rx Polarization	LHCP and RHCP (Simultaneous)	
	EIRP @ Psat	54 dBW	56 dBW
	Tx Polarization	LHCP or RHCP (Switchable)	
X-Band Rx [7.900 – 8.500 GHz]	G/T Mid-Band, 5° Elevation, Clear Sky, +20°C, Continental	N/A	>30.5 dB/K
	Rx Polarization		LHCP + RHCP
	Specific Filtering		Included – Radar Low Pass Filter
Ka-Band Rx [25.500 – 27.000 GHz]	G/T Mid-Band, 5° Elevation, Clear Sky, +20°C, Continental	>30.5 dB/K	>35 dB/K
	Rx Polarization	LHCP and RHCP (Simultaneous)	
Operational Modes	Auto-Track Mode	Single Channel Monopulse – Triband/Polarization Switchable in each band (Safran Data Systems Patented)	
Accuracy	Tracking Accuracy	0.03° rms	0.05° rms
	Pointing Accuracy	0.10° rms	0.08° rms
Environmental Conditions	Operating Wind	90 km/h (56 mi/h) gust	
	Survival Wind	180 km/h (112 mi/h)	200 km/h (125 mi/h)
	Operating Temperature	-20° C to +50° C (-4° F to +122° F) • -40° C to +50° C (-40° F to +122° F) with Available Options: Winter Package, Deicing, Radome	

## ▶ PEDESTAL SPECIFICATIONS

### Tracking Any Satellite from 400km (250 miles) Altitude

Azimuth Travel Range .....	540°
Elevation Travel Range .....	0°-90° + Train Axis
Angular Velocity .....	12°/s El - 10°/s Az
Angular Acceleration .....	10°/s <sup>2</sup> El / 10°/s <sup>2</sup> Az

## ▶ BASEBAND



### The Space Community Standard

TT&C Modem .....	Cortex CRT
High Rate Demodulator .....	Cortex HDR



## PRO Series Highest Quality, Best Performance & Ultimate Service Level

### GLOBAL SALES

5, Avenue des Andes - CS 90101 - 91978 Courtaboeuf Cedex - FRANCE - Tel.: +33 1 69 82 78 00 - Email: sales.sdsy@safrangroup.com

### USA

3005 Business Park Dr - Norcross, GA 30071 - USA - Tel.: +1 770 753 4017 - Email: sales@SafranDataSystemsUS.com

